



YBE1FB6



ERAI		Unit	CTN/CTG-328BRM	CTN/CTG-335BRM	CTN/CTG-356BRM	CTN/CTG-371BRM
Indoor unit reference			CTN-328BRM	CTN-335BRM	CTN-356BRM	CTN-371BRM
Outdoor unit reference			CTG-328BRM	CTG-335BRM	CTG-356BRM	CTG-371BRM
EAN code indoor unit			5205022021872	5205022021896	5205022021919	5205022021933
EAN code outdoor unit			5205022021889	5205022021902	5205022021926	5205022021940
Pdesignc		kW	2.7	3.5	5.1	6.5
Pdesignh (average zone)		kW	2.7	3.2	4.1	5.0
Pdesignh (warmer zone)		kW	2.9	3.5	4.3	5.7
Cooling capacity		Btu/h	9212 (2730-12966)	11976 (3388-15354)	17401 (3412-21837)	22200 (3.400-26.600)
		kW	2.70 (0.80-3.80)	3.51 (0.70-4.50)	5.10 (1.0-6.40)	6.45 (1.0-7.8)
Heating capacity		Btu/h	10236 (3071-14501)	13000 (2218-16719)	19107 (3753-23884)	22200 (5.290-30.700)
		kW	3.0 (0.90-4.25)	3.81 (0.65-4.90)	5.60 (1.10-7.0)	6.5 (1.55-9.0)
Cooling	SEER		8.5	8.5	8.5	8.5
	Cooling energy class		A+++	A+++	A+++	A+++
Heating	SCOP average zone		4.6	4.6	4.6	4.3
	Energy class average zone		A++	A++	A++	A+
	SCOP warmer zone		5.7	5.6	5.8	6.0
	Energy class warmer zone		A+++	A+++	A+++	A+++
Rated voltage / rated frequency / phase*		V/Hz/PH	220-240/50/1	220-240/50/1	220-240/50/1	220-240/50/1
Cooling	Annual electricity consumption (QCE)	kWh/a	111	144	210	268
	Power input**	kW	0.67	0.88	1.42	1.7
	Current	A	3.10	4.10	6.40	7.5
Heating	Annual electricity consumption average zone (QHE)	kWh/a	822	974	1248	1628
	Annual electricity consumption warmer zone (QHE)	kWh/a	712	875	1038	1330
	Power input**	kW	0.68	0.95	1.36	1.7
	Current	A	3.20	4.50	6.20	7.5
Dehumidification		L/h	0.8	1.4	1.8	2.4
Air flow volume (L/M/H/SH)		m3/h	180/390/420/440/470/540/570/610	320/430/460/500/530/570/600/720	450/550/600/620/650/760/880/1000	280/400/450/520/580/760/850/1000
Sound power level of indoor unit (SL/L/M/H/SH)		dB(A)	33/36/37/40/45/48/51/58	33/38/44/46/49/51/53/60	38/41/44/49/52/55/57/60	37/43/47/51/53/55/57/64
Sound pressure level of indoor unit (SL/L/M/H/SH)***		dB(A)	19/22/23/26/31/34/37/38	19/24/30/32/35/37/39/43	23/26/29/34/37/40/42/45	23/29/33/37/39/41/43/48
Sound power level of outdoor unit (HI)		dB(A)	61	64	65	70
Sound pressure level of outdoor unit (HI)***		dB(A)	50	53	59	58
Indoor unit	Unit dimensions (WxHxD)	mm	837 x 293 x 200	837 x 293 x 200	993 x 311 x 222	993 x 311 x 222
	Package dimensions (WxHxD)	mm	909 x 276 x 366	909 x 276 x 366	1067 x 386 x 300	1050 x 377 x 280
	Net/gross weight	kg	9.5/11.5	9.5/11.5	13/15.5	13/16
	Shielded communication cable (between IDU & ODU)	qty x mm	3x1.5+T	3x1.5+T	3x1.5+T	3x1.5+T
Outdoor unit	Unit dimensions (WxHxD)	mm	732 x 555 x 330	802 x 555 x 350	873 x 555 x 376	958 x 660 x 402
	Package dimensions (WxHxD)	mm	791 x 590 x 373	869 x 594 x 395	948 x 591 x 428	1029 x 715 x 453
	Net/gross weight	kg	25 / 27.5	25 / 27.5	37/40	42.5/47
	Power cable	qty x mm	2x2.5+T	2x2.5+T	2x2.5+T	2x2.5+T
Pipe	Liquid	mm (inch)	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")
	Gas	mm (inch)	9.53 (3/8")	9.53 (3/8")	12.7 (1/2")	15.88 (5/8")
	Maximum pipe length without adding refrigerant	m	5	5	5	5
	Maximum pipe length with adding refrigerant	m	15	15	25	25
	Maximum pipe height	m	10	10	10	10
Refrigerant charge (R32)		g	530	570	850	1300
Filter			High-density pre-filter - triple action filter (HEPA/silver ion/biological sterilization) - activated carbon			
Operation temperature limit	Cooling	°C	-15 ~ 50	-15 ~ 50	-15 ~ 50	-15 ~ 50
	Heating	°C	-25 ~ 30	-25 ~ 30	-25 ~ 30	-15 ~ 30

Harmonised standard: EN 14511 : 2007, EN 12102 - Global Warming Potential (GWP)

Note: *The power supply is on the outdoor unit ** The technical data comply with the UNI EN 14511/2004 standard *** Measured in free field



YBE1FB6



The versatile air conditioner

The Toyotomi ERAI is designed with respect for the environment and human beings. It offers maximum environmental comfort, intelligent functions, and voice control technology. The ionizer, enhanced sterilization with triple filtration (Hepa/Silver Ions/Biological), activated carbon filter, and self-cleaning functions Self Clean and Autoclean provide a perfectly clean environment while ensuring high efficiency and energy savings.

Erai ALL DC INVERTER

- | | | |
|---|-------------------------------------|--|
| Energy efficiency class A+++ / A+++ SEER 8.5 / SCOP 6.0 | Wi-Fi Function | Compatible with Google Home and Amazon Alexa |
| R32 refrigerant | Soft Start Function | Sleep Mode |
| "Save Energy" operating mode | Turbo Function | Cable Thermostat* |
| Heating mode at 8°C | Automatic Restart | High Density Pre-Filter |
| Remote control with Hotel Function* | Dehumidification Mode | Triple Action Filter |
| Key-card Control System* | Lock Function | Ionizer |
| I Sense Function | LED On/Off Function for Indoor Unit | Activated Carbon Filter |
| Smart preheating "SP" | Automatic Horizontal Oscillation | Self-Cleaning Function |
| Smart defrost | Automatic Vertical Oscillation | Blue Fins Treatment |
| Grille with position memory | Self-diagnosis System | Auto Cleaning |
| Timer Function | Smart Home Function | |

*Optional